

▶ Series 400 Braided Sleeving

DESCRIPTION



NOR · FAB Series 400 braided sleeving is manufactured in one style and two wall thicknesses. It is made using para-aramid fibers spun over a strong fiberglass core yarn.



APPLICATIONS



- ◆ **Electrical Leads**
- ◆ **Cables and Other Conductors to Provide Abrasion Resistance as well as Fire Protection**
- ◆ **Many Other Uses**

FEATURES



- ◆ **Inherently Flame Resistant**
- ◆ **DREF Yarn Construction**
- ◆ **Excellent Strength and Abrasion Resistance**
- ◆ **Good Flexibility**
- ◆ **Good Chemical Resistance**
- ◆ **Excellent Mildew Resistance**
- ◆ **Heat Resistant up to 650°F**



Norfab Corporation “Heat Resistant Textiles”
45 Primrose Drive
Laconia, New Hampshire USA
Phone: 1-866-524-2552
Fax: 1-866-924-3526
www.Amatex.com

▶ Braided Sleeving

Series 400 1/16" Wall Thickness				
Style Number	Size ID	Feet./LB	15# Spool (Ft/Spool)	25# Spool (Ft/Spool)
400-0125-2	1/8"	140.0	2,100	3,500
400-0250-2	1/4"	86.0	1,290	2,150
400-0375-2	3/8"	42.0	630	1,050
400-0500-2	1/2"	40.0	600	1,000
400-0625-2	5/8"	31.0	465	775
400-0750-2	3/4"	28.0	420	700
400-0875-2	7/8"	24.6	369	615
400-1000-2	1"	23.3	350	583
400-1250-2	1 1/4"	21.0	315	525
400-1500-2	1 1/2"	15.5	232	387
400-1750-2	1 3/4"	12.0	180	300
400-2000-2	2"	11.5	172	287
400-2250-2	2 1/4"	10.5	157	262

Series 400 1/8" Wall Thickness				
Style Number	Size ID	Feet./LB	15# Spool (Ft/Spool)	25# Spool (Ft/Spool)
400-1625-3	1 5/8"	10.1	152	253
400-2500-3	2 1/2"	7.0	105	175
400-3000-3	3"	6.1	92	153
400-4000-3	4"	3.6	54	90
400-4500-3	4 1/2"	3.4	51	85
400-5000-3	5"	2.8	42	70

25# Spools are standard - 15# Spools adds 10% to cost
All data +/- 10%

Other sizes may be available, Minimums may apply.



Norfab Corporation "Heat Resistant Textiles"
45 Primrose Drive
Laconia, New Hampshire USA
Phone: 1-866-524-2552
Fax: 1-866-924-3526
www.Amatex.com